

Specifications & Description

Max Flow Rate (mL/min)	5850
Min Flow Rate (mL/min)	0.85
Min Motor RPM (rpm)	50
Max Motor RPM (rpm)	5000
Motor Enclosure Type	Painted steel and ABS plastic
Enclosure IP Rating	IP 22
Remote Control Input	Start/stop
Power (VAC)	230
Power (Hz)	50/60
Duty Cycle Continuous	Yes
Width (in)	7.2
Width (cm)	18.3
Length (in)	9.1
Length (cm)	23
Height (in)	5.3
Height (cm)	13.4
Motor hp	1/20

2
YEAR
Warranty

KEY FEATURES

- 100:1 speed-control range controls flow over a wide range
- Maximum continuous-duty flow rates possible with Micropump® A-mount pump heads
- Simple operation with single-turn speed control
- Separate power switch enables you to maintain speed setting when turning drive on/off; front-panel LED indicates power on
- Remote control of start/stop via DB9 connector on back of drive
- Maximum flow rate of 5,850 mL/min
- Powered by 230VAC

MORE ABOUT THIS ITEM

Compact, cost-effective drive offers simple variable speed control for many fluid handling applications from general transfer to filtration to chemical injection. Couple with an A-mount gear pump head for pulseless fluid flow.